



Pipe Size	MAXIMUM LOAD RTG. (LBS)	A	B	C
	On Flat Surface (a)			
6	1000	9	6	1/2
8	1250	9	6	1/2
10	1550	9	6	5/8
12	2250	9	6	5/8
14	2780	9	6	5/8
16	3300	9	6	3/4
18	3600	9	6	3/4
20	3800	9	6	3/4
24	4100	9	6	1
30	4500	9	6	1
36	4500	9	6	1
42	4500	9	6	1

TABLE I

Contact factory for other dimensions, temperatures, and loads. Available in all insulation thicknesses.

Note: For higher load ratings, see A7400, B1100

The load ratings represent average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. Dimensions and ratings are subject to change without notice. Contact factory for current information.

To develop maximum load rating, width of support surface should be at least 1/2 of dimension "B" in Table I.

<p><b>Application:</b></p> <p>Model A7200 is designed for use on:</p> <ul style="list-style-type: none"> <li>· Hot Water      · Vacuum      · Gas</li> <li>· Cold Water    · Steam        · Air</li> <li>· Chilled Water</li> <li>· Dual Temperature</li> </ul> <p>Intended for installation on:</p> <ul style="list-style-type: none"> <li>· Flat Surfaces</li> <li>· Pipe rolls, see A8200</li> <li>· Clevis hangers, see A9000</li> </ul> <p>Temperature Range: +40°F to +1200°F</p> <p>Note: Up to 1700°F available upon request.</p>	<p><b>Features:</b></p> <ul style="list-style-type: none"> <li>· Compact</li> <li>· Easy Installation</li> <li>· Eliminates welding to pipe</li> <li>· Copper tubing sizes available</li> <li>· Minimizes heat-loss and/or condensation</li> <li>· Insulating structural inserts for load transfer</li> <li>· Overlapping galvanized sheet metal jacket</li> <li>· Other I.D.'s and/or O.D.'s available on request</li> <li>· Load distribution plate integral with bottom jacket</li> </ul> <p>Performance Test Results on File: Available upon request</p>	<p><b>Material Data:</b></p> <ul style="list-style-type: none"> <li>· A7200: Applicable PSI spec. doc.: No. 205.</li> <li>· Insulation: Calcium Silicate asbestos-free, treated with water repellent.</li> <li>· Jackets: Galvanized Steel ASTM A-527.</li> <li>· Structural Inserts: High-density calcium silicate asbestos-free, treated with water repellent.</li> <li>· Load distribution Plate: Carbon steel ASTM A-36</li> <li>· Coating: Primer coated or hot-dip galvanized. Other coatings available upon request.</li> <li>· Glue: Industrial contact adhesive.</li> </ul> <p>Formal Submittal Sheets available</p>
---	--	---