



Dimensions and ratings are subject to change without notice. Contact us for current information.  
Available in all insulation thickness.

**Note:**

- For small bore welded tee anchor, see: C1000
- For large bore "no moment" anchor, see: C2100
- For insulated friction anchor, see: C3000
- For insulated positive anchor, see: C4000

Pipe Size	A	C	D	E	F	G	Insulation Thickness						
							1"	2"	3"	4"	5"	6"	7"
							B	B	B	B	B	B	B
8	6	4	0.69	9	12	0.38	4	4	6	6	8	8	10
10	6	4	0.69	9	12	0.38	4	4	6	6	8	8	10
12	6	4	0.81	9	12	0.38	4	4	6	6	8	8	10
14	6	4	0.81	9	12	0.38	4	4	6	6	8	8	10
16	6	4	0.81	9	12	0.38	4	6	6	8	8	10	10
18	9	6.5	0.94	15	18	0.5	4	6	6	8	8	10	10
20	9	6.5	0.94	15	18	0.5	4	6	6	8	8	10	10
24	9	6.5	0.94	15	18	0.5	4	6	6	8	8	10	10
30	12	9	1.06	15	18	0.5	4	6	6	8	8	10	10

**Application:**

Model C2000 and C2030 are designed for use on:  
· Pipe Sizes through 8" through 30"

Model No.      For use with Pipe Material

C2000	Carbon Steel
C2010	Chrome-Moly
C2020	Carbon Silicon
C2030	Stainless

**Features:**

- Supplied with bolt holes for choice of bolting or welding to support structure.
- Bottom-of-pipe to top-of-steel matches base mounted insulated supports. See "B" Series.
- Broad selection of materials to match pipe material and eliminate galvanic action.
- Slots in central web for insulation banding.

**Material Data:**

- **C2000:** A36 Carbon Steel.
- **C2010:** A387 Gr. 23 Chrome-Moly Steel.
- **C2020:** A515 Gr. 70 Carbon Silicon Steel.
- **C2030:** 304L Stainless Steel.
- **Primer Coating:** Primer coated or hot dipped galvanized. Other coatings available upon request.

Other materials available upon request.

**Formal submittal sheets available**